



UNITED STATES PATENT AND TRADEMARK OFFICE

UNITED STATES DEPARTMENT OF COMMERCE
United States Patent and Trademark Office
Address: COMMISSIONER FOR PATENTS
P.O. Box 1450
Alexandria, Virginia 22313-1450
www.uspto.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
10/780,526	02/17/2004	Milan Pophristic	EMCORE 3.0-084	1505
530	7590	11/15/2006	EXAMINER	
LERNER, DAVID, LITTENBERG, KRUMHOLZ & MENTLIK 600 SOUTH AVENUE WEST WESTFIELD, NJ 07090			GEBREMARIAM, SAMUEL A	
			ART UNIT	PAPER NUMBER
			2811	

DATE MAILED: 11/15/2006

Please find below and/or attached an Office communication concerning this application or proceeding.

Office Action Summary

Application No.

10/780,526

Applicant(s)

POPHRISTIC ET AL.

Examiner

Samuel A. Gebremariam

Art Unit

2811

-- The MAILING DATE of this communication appears on the cover sheet with the correspondence address --

Period for Reply

A SHORTENED STATUTORY PERIOD FOR REPLY IS SET TO EXPIRE 3 MONTH(S) OR THIRTY (30) DAYS, WHICHEVER IS LONGER, FROM THE MAILING DATE OF THIS COMMUNICATION.

- Extensions of time may be available under the provisions of 37 CFR 1.136(a). In no event, however, may a reply be timely filed after SIX (6) MONTHS from the mailing date of this communication.
- If NO period for reply is specified above, the maximum statutory period will apply and will expire SIX (6) MONTHS from the mailing date of this communication.
- Failure to reply within the set or extended period for reply will, by statute, cause the application to become ABANDONED (35 U.S.C. § 133). Any reply received by the Office later than three months after the mailing date of this communication, even if timely filed, may reduce any earned patent term adjustment. See 37 CFR 1.704(b).

Status

- 1) ☒ Responsive to communication(s) filed on 06 September 2006.
- 2a) ☐ This action is **FINAL**. 2b) ☒ This action is non-final.
- 3) ☐ Since this application is in condition for allowance except for formal matters, prosecution as to the merits is closed in accordance with the practice under *Ex parte Quayle*, 1935 C.D. 11, 453 O.G. 213.

Disposition of Claims

- 4) ☒ Claim(s) 1-17, 19-36 and 71-73 is/are pending in the application.
- 4a) Of the above claim(s) _____ is/are withdrawn from consideration.
- 5) ☐ Claim(s) _____ is/are allowed.
- 6) ☒ Claim(s) 1-17, 19-36 and 71-73 is/are rejected.
- 7) ☐ Claim(s) _____ is/are objected to.
- 8) ☐ Claim(s) _____ are subject to restriction and/or election requirement.

Application Papers

- 9) ☐ The specification is objected to by the Examiner.
- 10) ☐ The drawing(s) filed on _____ is/are: a) ☐ accepted or b) ☐ objected to by the Examiner.
Applicant may not request that any objection to the drawing(s) be held in abeyance. See 37 CFR 1.85(a).
Replacement drawing sheet(s) including the correction is required if the drawing(s) is objected to. See 37 CFR 1.121(d).
- 11) ☐ The oath or declaration is objected to by the Examiner. Note the attached Office Action or form PTO-152.

Priority under 35 U.S.C. § 119

- 12) ☐ Acknowledgment is made of a claim for foreign priority under 35 U.S.C. § 119(a)-(d) or (f).
- a) ☐ All b) ☐ Some * c) ☐ None of:
1. ☐ Certified copies of the priority documents have been received.
 2. ☐ Certified copies of the priority documents have been received in Application No. _____.
 3. ☐ Copies of the certified copies of the priority documents have been received in this National Stage application from the International Bureau (PCT Rule 17.2(a)).

* See the attached detailed Office action for a list of the certified copies not received.

Attachment(s)

- | | |
|--|---|
| 1) <input type="checkbox"/> Notice of References Cited (PTO-892) | 4) <input type="checkbox"/> Interview Summary (PTO-413)
Paper No(s)/Mail Date. _____ |
| 2) <input type="checkbox"/> Notice of Draftsperson's Patent Drawing Review (PTO-948) | 5) <input type="checkbox"/> Notice of Informal Patent Application |
| 3) <input type="checkbox"/> Information Disclosure Statement(s) (PTO/SB/08)
Paper No(s)/Mail Date _____ | 6) <input type="checkbox"/> Other: _____ |

DETAILED ACTION

Request for Continued Examination

1. A request for continued examination (RCE) under 37 CFR 1.114, including the fee set forth in 37 CFR 1.17(e), was filed in this application after final rejection. Since this application is eligible for continued examination under 37 CFR 1.114, and the fee set forth in 37 CFR 1.17(e) has been timely paid, the finality of the previous Office action has been withdrawn pursuant to 37 CFR 1.114. Applicant's submission filed on 9/6/2006 has been entered. An action on the RCE follows.

2. The amendment filed on 8/7/2006 has been entered.

Claim Rejections - 35 USC § 112

3. The following is a quotation of the second paragraph of 35 U.S.C. 112:

The specification shall conclude with one or more claims particularly pointing out and distinctly claiming the subject matter which the applicant regards as his invention.

4. Claims 1, 17 and 71 are rejected under 35 U.S.C. 112, second paragraph, as being indefinite for failing to particularly point out and distinctly claim the subject matter which applicant regards as the invention. It is unclear what the structural relationship is between the modulation doped layer and the resulting modulation doped layer. It appears from the claim that there are two types of modulation doped layers. Further it is unclear what the limitation of an overall doping concentration mean.

With regards to claim 71, it is unclear what the structural relationship is between an upper layer structure and the resulting upper layer structure. It appears from the claim that there are two types of upper layer structures. Further it is unclear what the limitation of an overall doping concentration mean.

Claim Rejections - 35 USC § 103

5. The following is a quotation of 35 U.S.C. 103(a) which forms the basis for all obviousness rejections set forth in this Office action:

(a) A patent may not be obtained though the invention is not identically disclosed or described as set forth in section 102 of this title, if the differences between the subject matter sought to be patented and the prior art are such that the subject matter as a whole would have been obvious at the time the invention was made to a person having ordinary skill in the art to which said subject matter pertains. Patentability shall not be negated by the manner in which the invention was made.

6. Claims 1-2 and 4-14 are rejected under 35 U.S.C. 103(a) as being unpatentable over Nakamura et al., Pub. No. US 2003/0010993 in view of Parikh et al, WO 03/026021.

Regarding claim 1, as best the examiner is able to ascertain the claimed invention Nakamura teaches (fig. 1) a method of forming a semiconductor layer structure, the method comprising: forming a modulation doped layer structure (4) atop at least a portion of another layer (3) by forming at least one sub-layer of doped nitride semiconductor (refer to paragraph [0054]) and at least one sub-layer undoped nitride semiconductor (refer to paragraph [0054]) atop the at least portion of the another layer (3).

Nakamura does not explicitly state that the overall modulation-doped layer structure has an overall doping concentration of at most $2 \times 10^{16} \text{cm}^{-3}$.

Parikh teaches an n-doped GaN doped with impurities concentration in the range of 5×10^{14} to 5×10^{17} per cm^{-3} (page 21) in the process of forming a gallium nitride based diodes.

Therefore it would obvious to one of ordinary skill in the art at the time the invention was made to adjust the overall modulation doped layer structure concentration

as taught by Parikh in the process of Nakamura in order to form a high quality film with improved crystallinity.

Furthermore parameters such as concentration in the art of semiconductor manufacturing process are subject to routine experimentation and optimization to achieve the desired device characteristics during fabrication.

- Therefore, it would have been obvious to one of ordinary skill in the art at the time the invention was made to adjust the modulation doped layer concentration as claimed in the process of Nakamura in order to form a high quality film with improved crystallinity.

Regarding claim 2, Nakamura teaches substantially the entire claimed structure of claim 1 above including the forming step includes forming alternating sub-layers of doped nitride semiconductor and undoped nitride semiconductor (layer 4, [0054]) atop the at least portion of the another layer (3).

Regarding claim 4, Nakamura teaches substantially the entire claimed structure of claim 1 above except explicitly stating that diffusing dopants from the sub-layer of doped nitride semiconductor into the sub-layer of undoped nitride semiconductor to form the modulation doped layer, the doped layer having a doping concentration that is substantially uniform.

It is conventional in the art to form doped regions by diffusing dopants from one layer to another. Furthermore parameters such as doping level in the art of semiconductor manufacturing process are subject to routine experimentation and optimization to achieve the desired device characteristics during fabrication.

It would have been obvious to one of ordinary skill in the art at the time the invention was made to dope the undoped layer as claimed in order to form a layer with improved conductivity.

Regarding claims 5 and 6, Nakamura teaches substantially the entire claimed structure of claim 1 above including the modulation-doped layer includes a gallium nitride-based semiconductor and the modulation-doped layer included GaN ([0054]).

Regarding claim 7, Nakamura teaches substantially the entire claimed structure of claim 1 above including the modulation-doped layer is n-type (the modulation doped layer 4 has silicon as dopant hence n-type [0054]).

Regarding claim 8, Nakamura teaches substantially the entire claimed structure of claim 1 above including the modulation-doped layer has a doping concentration of at least $4 \times 10^{15} \text{cm}^{-3}$ (the modulation doped layer has more than what is claimed, refer to [0054]).

Regarding claims 9-11, Nakamura teaches substantially the entire claimed structure of claim 1 above including the modulation-doped layer has a thickness of at least $0.2 \mu\text{m}$, or at most $10 \mu\text{m}$ (the modulation doped layer has a thickness of $1 \mu\text{m}$, refer to [0054]) and the doped sub-layer is at least $0.005 \mu\text{m}$ ([0054]).

Regarding claims 12-13, Nakamura teaches substantially the entire claimed structure of claim 1 above except explicitly stating that the modulation-doped layer has a thickness of most $0.1 \mu\text{m}$ or the undoped sub-layer has a thickness of at least $0.005 \mu\text{m}$.

Parameters such as thickness in the art of semiconductor manufacturing process are subject to routine experimentation and optimization to achieve the desired device characteristics during fabrication.

Therefore, it would have been obvious to one of ordinary skill in the art at the time the invention was made to adjust the thickness of the modulation doped layer as claimed in order to form a high quality film with improved crystallinity.

Regarding claim 14, Nakamura teaches substantially the entire claimed structure of claim 1 above including the undoped sub-layer of the modulation doped layer has a thickness of at most 0.1 μm (the undoped sub-layer has a thickness of 0.002 μm [0054]).

7. Claim 3 is rejected under 35 U.S.C. 103(a) as being unpatentable over Nakamura, Parikh and in view of D' Evelyn et al., Pub. No. US 2002/0155634.

Nakamura teaches substantially the entire claimed process of claim 1 above except explicitly stating that the forming step is carried out by process selected from the group consisting of reactive sputtering, metal organic chemical vapor deposition (MOCVD), molecular beam epitaxy (MBE) and atomic layer epitaxy.

D' Evelyn teaches forming a nitride-based layer by MOCVD (paragraph [0063]).

It would have been obvious to one of ordinary skill in the art at the time the invention was made to incorporate the process of using MOCVD taught by D' Evelyn to form the modulation doped layer in the process of Nakamura in order to improve better coverage during deposition.

Art Unit: 2811

8. Claims 15 and 16 are rejected under 35 U.S.C. 103(a) as being unpatentable over Nakamura, Parikh and in view of Lee et al., Pub. No. US 2001/0034116.

Regarding claim 15, Nakamura teaches substantially the entire claimed structure of claim 1 above except explicitly stating that forming a Schottky junction includes forming a metal contact layer atop the modulation doped layer.

It is conventional to form Schottky junction and is also taught by Lee (fig. 8) forming a Schottky contact/junction by forming a metal contact (44) in the process of forming a semiconductor device with a Schottky contact.

It would have been obvious to one of ordinary skill in the art at the time the invention was made to incorporate the Schottky junction taught by Lee in the process of Nakamura in order to form a rectifying junction with an excellent electrical characteristics.

Regarding claim 16, Nakamura teaches substantially the entire claimed structure of claims 1 and 15 above except explicitly stating forming an ohmic contact on another portion of the another layer.

It is conventional to form an ohmic contact and is also taught by Lee (fig. 8) forming an ohmic contact by forming contact (45) in the process of forming a semiconductor device with an ohmic contact.

It would have been obvious to one of ordinary skill in the art at the time the invention was made to incorporate the ohmic contact taught by Lee in the process of Nakamura in order to form a contact with an excellent electrical characteristics.

Art Unit: 2811

9. Claims 17 and 19-35 are rejected under 35 U.S.C. 103(a) as being unpatentable over Nakamura, in view of D' Evelyn et al., Pub. No. US 2002/0155634 and in further view of Parikh.

Regarding claim 17, as best the examiner is able to ascertain the claimed invention Nakamura teaches (fig. 1) forming a modulation doped layer structure (4) atop at least a portion another layer (3) by forming alternating sub-layers of doped nitride semiconductor (layer 4, [0054]) and undoped nitride semiconductor (layer 4, [0054]) atop the at least portion of the another layer (3);

Nakamura does not explicitly teach the resulting modulation doped layer structure has an overall doping concentration of at most $2 \times 10^{16} \text{cm}^{-3}$, forming a metallic contact layer atop at least part of the modulation doped layer to form a Schottky junction therewith; and forming at least one further metallic contact layer on at least part of the another layer in substantially ohmic contact therewith or a ratio of an on-resistance of the Schottky diode to a breakdown voltage of the Schottky diode is at most $2 \times 10^{-5} \Omega \cdot \text{cm}^2 / \text{V}$.

D' Evelyn teaches (fig. 4) a method of forming a Schottky diode, the method comprising: forming a metallic contact layer (310) atop at least part of a modulation doped layer (302, 314) to form a Schottky junction therewith (Schottky contact is formed between 210 and 302); and forming at least one further metallic contact layer (312) on at least part of another layer (310) in substantially ohmic contact therewith (ohmic contact is formed between 312 and 316).

D' Evelyn does not explicitly teach that a ratio of an on-resistance of the Schottky diode to a breakdown voltage of the Schottky diode is at most $2 \times 10^{-5} \Omega \cdot \text{cm}^2 / \text{V}$.

Parikh teaches Parikh teaches an n-doped GaN doped with impurities concentration in the range of 5×10^{14} to 5×10^{17} per cm^{-3} (page 21) in the process of forming a gallium nitride based diodes and breakdown voltage fields of $2 \times 10^6 \text{ V/cm}$ for a GaN based device. By finding the ratio of the on-resistance to the breakdown voltage one can get the ratio of an on-resistance of the Schottky diode to a breakdown voltage of the Schottky diode.

Therefore it would obvious to one of ordinary skill in the art at the time the invention was made to adjust the overall modulation doped layer structure concentration as taught by Parikh in the process of Nakamura in order to form a high quality film with improved crystallinity.

Furthermore parameters such as concentration in the art of semiconductor manufacturing process are subject to routine experimentation and optimization to achieve the desired device characteristics during fabrication.

Therefore, it would have been obvious to one of ordinary skill in the art at the time the invention was made to adjust the modulation doped layer concentration as claimed in the process of Nakamura in order to form a high quality film with improved crystallinity.

It would also have been obvious to one of ordinary skill in the art at the time the invention was made to incorporate the process of forming a metallic contact layer atop

at least part of the modulation doped layer to form a Schottky junction; and forming at least one further metallic contact layer on at least part of the another layer in substantially ohmic contact as taught by D' Evelyn in the process of Nakamura in order to form a photodetector device with improved sensitivity.

Furthermore it would have been obvious to one of ordinary skill in the art at the time the invention was made to adjust the ratio of on-resistance to the breakdown voltage as claimed in the combined process of Nakamura, D' Evelyn and Parikh in order to form a diode with better electrical characteristics. Since the combined process teaches the same layers as the claimed invention, the ratio of the on-resistance to the breakdown voltage would be closer to the claimed invention.

Furthermore parameters such as ratio of on-resistance to breakdown voltage in the art of semiconductor manufacturing process are subject to routine experimentation and optimization to achieve the desired device characteristics during fabrication.

Therefore, it would have been obvious to one of ordinary skill in the art at the time the invention was made to adjust the ratio of on-resistance to the breakdown voltage as claimed in the combined process of Nakamura, D' Evelyn and Parikh in order to form a diode with better electrical characteristics.

Regarding claim 19, Nakamura teaches substantially the entire claimed process of claim 17 above including the step of forming the modulation doped layer is carried out by MOCVD (D' Evelyn, paragraph [0063]).

Regarding claims 20 and 21, Nakamura teaches substantially the entire claimed process of claim 17 above including a gallium nitride-based semiconductor and includes GaN (D' Evelyn paragraph [0052]).

Regarding claim 22, Nakamura teaches substantially the entire claimed process of claim 17 above including the modulation-doped layer is n-type (D' Evelyn, fig. 4).

Regarding claims 23 and 24, Nakamura teaches substantially the entire claimed process of claim 17 above including the modulation doped has a thickness of at least $0.2\text{ }\mu\text{m}$ or at most $10\text{ }\mu\text{m}$ (D' Evelyn, layer 316 is in the range of $1\text{-}10\text{ }\mu\text{m}$).

Regarding claim 25, Nakamura teaches substantially the entire claimed process of claim 17 above including the doped sub-layer of the modulation doped layer has a thickness of at least $0.005\text{ }\mu\text{m}$ (D' Evelyn, layer 316 is in the range of $1\text{nm}\text{-}10\text{ }\mu\text{m}$).

Regarding claims 26-28, Nakamura teaches substantially the entire claimed process of claim 17 above except explicitly stating that the doped sub-layer modulation-doped layer has a thickness of at most $0.1\text{ }\mu\text{m}$, the undoped sub-layer has a thickness of at least $0.005\text{ }\mu\text{m}$ or at most $0.1\text{ }\mu\text{m}$.

Parameters such as thickness in the art of semiconductor manufacturing process are subject to routine experimentation and optimization to achieve the desired device characteristics during fabrication.

Therefore, it would have been obvious to one of ordinary skill in the art at the time the invention was made to adjust the thickness of both the doped and undoped sub-layers of the modulation doped layer as claimed in the process of Nakamura in order to form a high quality film with improved crystallinity.

Regarding claim 29, Nakamura teaches substantially the entire claimed process of claim 17 above including the first metal contact layer is nickel (D' Evelyn, [0053]).

Regarding claim 30, Nakamura teaches substantially the entire claimed process of claim 17 above except explicitly stating that the another layer comprises another doped layer of nitride semiconductor and the method further comprises forming the another layer atop a substrate prior to the step of forming the modulation doped layer atop the at least portion of the another layer, the modulation doped layer and the another layer being of the same conductivity type, the another layer being of the same conductivity type, the another layer being more highly doped than the modulation doped layer.

However Parikh teaches (fig. 1) the use of highly doped layer (12) formed over a substrate (11) in the process of forming a nitride based diode.

It would have been obvious to one of ordinary skill in the art at the time the invention was made to incorporate the substrate portion of the diode structure as taught by Parikh in the process of Nakamura in order to provide a better crystal structure transition between the substrate and the remainder of the device. Therefore the combined process of Nakamura, D' Evelyn and Parikh teaches the another layer comprises another doped layer of nitride semiconductor (12, Parikh) and the method further comprises forming the another layer atop a substrate (11, Parikh) prior to the step of forming the modulation doped layer (4, Nakamura) atop the at least portion of the another layer (3, Nakamura), the modulation doped layer and the another layer being of the same conductivity type (n), the another layer being of the same conductivity

type (n), the another layer being more highly doped than the modulation doped layer (n^+ verses n).

Parameters such as concentration in the art of semiconductor manufacturing process are subject to routine experimentation and optimization to achieve the desired device characteristics during fabrication.

Therefore, it would have been obvious to one of ordinary skill in the art at the time the invention was made to adjust the modulation doped layer concentration and another doped layer as claimed in the process of D' Evelyn in order to form a high quality film with improved crystallinity.

Regarding claims 31-33, Nakamura teaches substantially the entire claimed process of claim 17 above including the another doped layer includes a gallium nitride-based (refer to [0052]) semiconductor, the another doped layer includes GaN ([0052]) and the another doped layer is n-type ([0052], D' Evelyn).

Regarding claim 34, Nakamura teaches substantially the entire claimed process of claim 17 except explicitly stating that the another doped layer has a doping concentration of at least $4E18\text{ cm}^{-3}$.

Parameters such as concentration in the art of semiconductor manufacturing process are subject to routine experimentation and optimization to achieve the desired device characteristics during fabrication.

Therefore, it would have been obvious to one of ordinary skill in the art at the time the invention was made to adjust the another doped layer concentration as claimed

in the process of Nakamura in order to form a high quality film with improved crystallinity.

Regarding claim 35, Nakamura teaches substantially the entire claimed process of claim 17 above including the substrate is selected from the group consisting of sapphire (Parikh page 7, lines 30 to page 8, lines 1-2).

10. Claims 71-73 are rejected under 35 U.S.C. 103(a) as being unpatentable over D' Evelyn in view of Parikh in further view of Nakamura.

Regarding claim 71, D' Evelyn teaches (fig. 4) a method of forming a Schottky diode, the method comprising: forming a lower layer of n-type doped nitride semiconductor (316) atop a substrate (306); forming an upper layer structure (314, 302) atop at least a portion of the lower layer of nitride semiconductor (316), the sub-layers being formed metal organic chemical vapor deposition (MOCVD, paragraph [0063]), forming a first metal contact layer (310) atop the upper layer of nitride semiconductor (302) such that a Schottky contact is formed (contact between 302 and 310); and forming a second metal contact layer (312) atop the lower layer of nitride semiconductor (316) such that an ohmic contact is formed (contact between 316 and 312).

D' Evelyn does not explicitly teach that forming the upper top layer structure by forming alternating sub-layers of n-type doped nitride semiconductor and undoped nitride semiconductor such that the resulting upper layer structure has an overall doping concentration of at most $2 \times 10^{16} \text{ cm}^{-3}$ or the lower layer of nitride semiconductor being more highly doped than the upper layer of nitride semiconductor and a ratio of an on-

Art Unit: 2811

resistance of said Schottky diode to a breakdown voltage of said Schottky diode is at most $2 \times 10^{-5} \Omega \cdot \text{cm}^2 / \text{V}$.

Nakamura teaches the advantage of forming alternating layers of doped and undoped sub-layers of nitride semiconductors (4) in the process of forming nitride based semiconductor device (fig. 1) with improved crystallinity.

Parikh teaches an n-doped GaN doped with impurities concentration in the range of 5×10^{14} to 5×10^{17} per cm^{-3} (page 21) in the process of forming a gallium nitride based diodes and the breakdown voltage fields of $2 \times 10^6 \text{ V/cm}$ for a GaN based device. By finding the ratio of the on-resistance to the breakdown voltage one can get the ratio of an on-resistance of the Schottky diode to a breakdown voltage of the Schottky diode.

Therefore it would have been obvious to one of ordinary skill in the art at the time the invention was made to incorporate the process of forming a super lattice of doped and undoped layer taught by Nakamura in the process of D' Evelyn in order to improve the crystallinity of the layers.

Furthermore it would have been obvious to one of ordinary skill in the art at the time the invention was made to adjust the upper layer doping layer concentration and the ratio of on-resistance to breakdown voltage as taught by Parikh in the process of D' Evelyn in order to form a high quality film with improved crystallinity. The combined process of D' Evelyn, Nakamura and Parikh would have the overall doping concentration layer of the resulting upper layer structure as claimed. Since the combined process of Nakamura, Parikh and D' Evelyn teaches the same layers as the

Art Unit: 2811

claimed invention, the ratio of the on-resistance to the breakdown voltage would be closer to the claimed invention.

Furthermore parameters such as concentration and ratio of on-resistance to breakdown voltage in the art of semiconductor manufacturing process are subject to routine experimentation and optimization to achieve the desired device characteristics during fabrication.

Regarding claim 72, D' Evelyn teaches substantially the entire claimed process of claim 71 above including the at least one of the upper layer (302) of nitride semiconductor and the lower layer (314) of nitride semiconductor includes a gallium nitride-based semiconductor (paragraph [0052]).

Regarding claim 73, D' Evelyn teaches substantially the entire claimed process of claim 71 above including at least one of the upper layer (302) of nitride semiconductor and the lower layer (314) of nitride semiconductor includes GaN (paragraph [0052]).

11. Claim 36 is rejected under 35 U.S.C. 103(a) as being unpatentable over Nakamura, D' Evelyn, Parikh in view of Sheu et al., US patent No. 6,712,478.

Regarding claim 36, Nakamura teaches substantially the entire claimed process of claim 17 above except explicitly stating that the ohmic metal contact layer is selected from the group consisting of aluminum/titanium/platinum/gold (Al/Ti/Pt/Au) and titanium/aluminum/platinum/gold (Ti/Al/Pt/Au).

However Sheu teaches (fig.3) where the ohmic metal contact layer (162) is formed of Ti/Al/Pt/Au in the process of forming light emitting device.

Therefore it would have been obvious to one of ordinary skill in the art at the time the invention was made to form the ohmic metal contact taught by Sheu in the process of Nakamura in order to reduce the contact resistance.

Response to Arguments

12. Applicant's arguments filed 8/7/2006 have been fully considered but they are not persuasive. With regards to claims 1-17 and 19-36, applicant argues that the reference by Nakamura and Parikh does not teach the resulting modulation doped layer structure having an overall doping concentration of at most $2 \times 10^{16} \text{ cm}^{-3}$. As stated above in the rejection, it is unclear what applicant is trying to say when stating an overall doping concentration. Since the modulation doped layer structure comprises of two layers, one doped and undoped, it is not clear what an overall doping concentration mean. Is applicant trying to say an average doping concentration? Further is not clear what it means when stating the resulting modulation doped structure.

Furthermore generally difference in concentration does not support the patentability of subject matter encompassed by the prior art unless there is evidence indicating such concentration or temperature is critical. "[W]here the general conditions of claim are disclosed in the prior art, it is not inventive to discover the optimum or workable ranges by routine experimentation." In re Aller, 220 F.2d 454, 105 USPQ 233, 235 (CCPA 1955). See also In re Hoeschele, 406 F.2d 1403, 160 USPQ 809 (CCPA 1969). For more recent cases applying this principle, see Merck & Co. Inc. v. Biocraft Laboratories Inc., 874 F.2d 804, 10 USPQ2d 1843 (Fed. Cir.), cert. Denied, 493 U.S. 975 (1989), and In re Kulling, 897 F.2d 1147, 14 USPQ2d 1056 (Fed. Cir. 1990).

Art Unit: 2811

11. The same argument as above applies to claims 71-73.

Conclusion

13. Any inquiry concerning this communication or earlier communications from the examiner should be directed to Samuel A. Gebremariam whose telephone number is (571)-272-1653. The examiner can normally be reached on 8:00am-4:30pm.

If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, Richard Elms can be reached on (571) 272-1869. The fax phone number for the organization where this application or proceeding is assigned is 571-273-8300.

Information regarding the status of an application may be obtained from the Patent Application Information Retrieval (PAIR) system. Status information for published applications may be obtained from either Private PAIR or Public PAIR. Status information for unpublished applications is available through Private PAIR only. For more information about the PAIR system, see <http://pair-direct.uspto.gov>. Should you have questions on access to the Private PAIR system, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free). If you would like assistance from a USPTO Customer Service Representative or access to the automated information system, call 800-786-9199 (IN USA OR CANADA) or 571-272-1000.

SAG

November 9, 2006

Douglas W. Owens 11/9/06

DOUGLAS W. OWENS
PRIMARY EXAMINER